



# GULL

## HIGH-EFFICIENCY LINEAR LUMINAIRE

### PRODUCT INFORMATION

Gull - an efficient solution to illuminate administrative and retail premises. Aesthetic design, different optics, and high flexibility allow creating unique and eye-catching designs while maintaining low glare and high illuminance levels. To perfectly fit the room and environment, Gull is available in custom lengths, CCT, CRI, and RAL colors. With this luminaire, we enable considerably high efficacy going up to 170 lm/W resulting in a significant reduction in energy consumption.

### APPLICATION

- Hotel halls
- Conference rooms
- Offices
- Corridors
- Aisle lighting

### FEATURES & BENEFITS

- Efficacy up to 170 lm/W
- Easy installation
- 2 diffusers: opal and diamond for low glare
- DALI control available


# GULL LINEAR LUMINAIRE




## GENERAL INFORMATION

SUPPLY VOLTAGE	198 – 264 V; 50-60 Hz
POWER FACTOR	>0.95
EFFICACY	155 – 170 lm/W
CCT	4000 ± 150 K (natural white)
CRI	>80
IP CLASS	IP20
RECOMMENDED HEIGHT	From 2.0 up to 5.0 meters
OPERATING TEMP.	-10 °C ~ +40 °C
STORAGE TEMP.	+10 °C ~ +50 °C
LIFETIME	L80B10 >100 000 h (Ta 25°C)
MOUNTING OPTIONS	suspended   surface
CERTIFICATION	CE and RoHS compliant
DIMENSIONS	1200 x 57.5 x 75 mm
WEIGHT	2.1 kg
WARRANTY	5 years

## LIGHT DISTRIBUTION GRAPH



— C0-180 - - C90-270 90°



— C0-180 - - C90-270 115°

## DIFFUSERS FOR LOW GLARE




Diamond diffuser



Opal diffuser

## MOUNTING ACCESSORIES



Stainless-steel surface mounting kit, included with the luminaire



Stainless-steel hanging kit, ordered separately; SKU - BLNP-HKIT

## ORDERING INFORMATION

SKU	DIFFUSER	BEAM ANGLE	POWER, W	LUMEN OUTPUT, LM	CCT, K	DALI CONTROL
BLNP-U-120A90840P20	diamond	90°	20W ± 5%	3300 ± 3%	4000 ± 150	-
BLNP-U-120A90840P20-DA	diamond	90°	20W ± 5%	3300 ± 3%	4000 ± 150	+
BLNP-U-120A90840P24	diamond	90°	24W ± 5%	4080 ± 3%	4000 ± 150	-
BLNP-U-120A90840P24-DA	diamond	90°	24W ± 5%	4080 ± 3%	4000 ± 150	+
BLNP-U-120A90840P28	diamond	90°	28W ± 5%	4710 ± 3%	4000 ± 150	-
BLNP-U-120A90840P28-DA	diamond	90°	28W ± 5%	4710 ± 3%	4000 ± 150	+
BLNP-M-120A120840P20	opal	115°	20W ± 5%	3170 ± 3%	4000 ± 150	-
BLNP-M-120A120840P20-DA	opal	115°	20W ± 5%	3170 ± 3%	4000 ± 150	+
BLNP-M-120A120840P26	opal	115°	26W ± 5%	4290 ± 3%	4000 ± 150	-
BLNP-M-120A120840P26-DA	opal	115°	26W ± 5%	4290 ± 3%	4000 ± 150	+
BLNP-M-120A120840P32	opal	115°	32W ± 5%	5200 ± 3%	4000 ± 150	-
BLNP-M-120A120840P32-DA	opal	115°	32W ± 5%	5200 ± 3%	4000 ± 150	+